




Infrared Pyrometer




measuring
•
monitoring
•
analysing

TIN-SH



- One of the smallest infrared sensors worldwide with 22:1 optical resolution
- Rugged and usable up to 180 °C ambient temperature without cooling
- Separate electronics with easy accessible programming keys and LCD backlit display
- Selectable analog output: 0/4 - 20 mA, 0 - 5 V, 0 - 10 V, thermocouple type K or J



T2

KOBOLD companies worldwide:

AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHINA, CZECHIA, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, SPAIN, SWITZERLAND, THAILAND, TUNISIA, TURKEY, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com



Description

The pyrometer TIN-SH is equipped with one of the world's smallest infrared sensors with a high optic resolution of 22:1. Additionally, it offers a high variability due to selectable analog outputs as well as several digital interfaces in the electronics box.

Technical Details

General Specifications

Material sensing head:	Stainless steel
Material electronic box:	Die casting zinc
Environmental rating:	IP 65 (NEMA-4)
Ambient temperature ¹⁾ :	-20 ... +180 °C -20 ... +85 °C (electronics)
Storage temperature:	-40 ... +130 °C (sensing head) -40 ... +85 °C (electronics)
Relative humidity:	10 - 95 %, non condensing
Vibration (sensor):	IEC 60068-2-6 (sinus shaped) IEC 60068-2-64 (broadband noise)
Shock (sensor):	IEC 60068-2-27 (25G and 50G)
Weight:	40 g (sensing head) 420 g (electronics)

Electrical Specifications

Outputs / analog:	Channel 1: 0 / 4 - 20 mA, 0 - 5 / 10 V, thermocouple J, K Channel 2: sensing head temperature (-20 ... +180 °C as 0 - 5 V or 0 - 10 V), alarm output
Output / alarm:	24 V / 50 mA (open collector)
Optional:	Relay: 2 x 60 V _{DC} / 42 V ACeff; 0.4 A; optically isolated
Outputs / digital (optional):	USB, RS232, RS485, Ethernet
Output impedances:	mA max. 500 Ω (with 8 - 36 V _{DC}) mV min. 100 kΩ load impedance thermocouple 20 Ω
Inputs:	Programmable functional inputs for external emissivity adjustment, ambient temperature compensation, trigger (reset of hold functions)
Cable length:	3 m
Power Supply:	8 - 36 V _{DC}
Current draw:	Max. 100 mA

Measurement Specifications

Temperature range (scalable via programming keys or software):	-50 ... +975 °C
Spectral range:	8 - 14 μm
Optical resolution (90 % energy):	22:1 (precision glass optics)
CF-lens (optional):	0.6 mm @ 10 mm (with LT22)
System accuracy ^{2) 3)} (at ambient temp. 23 ± 5 °C):	± 1 % or ± 1 °C
Repeatability ^{2), 3)} (at ambient temp. 23 ± 5 °C):	± 0.5 % or ± 0.5 °C
Temperature resolution (display):	0.1 K
NETD ^{3) 4)} :	0.05 K (LT22 / LT15) 0.1 K (LT02)
Response time:	150 ms (95 %)
Emissivity/ Gain (adjustable via programming keys or software):	0.100 - 1.100
Transmissivity/ Gain (adjustable via programming keys or software):	0.100 - 1.100
Signal processing (parameter adjustable via programming keys or software, respectively):	Peak hold, valley hold, average; extended hold function with threshold and hysteresis
Software:	for Windows®, download at www.kobold.com/qr/TIN

¹⁾ The LCD displays capacity may be limited at ambient temperatures below 0 °C

²⁾ Whichever is greater

³⁾ At object temperatures > 0 °C, ε = 1


⁴⁾ At time constant 200 ms and T_{obj} 25 °C

Order Details Model TIN-SH (Example: TIN-SHN7S2030)


Model	Measuring range	Analog output	Optics / Spectral range	Cable length	Laser
TIN-SH = High Accuracy pyrometer (2-part)	N7 = -50...+975 °C	S = Channel 1: 0/4 - 20 mA, 0 - 5/10V, Thermoelement J, K; Channel 2: Sensing Head Temperature (-20...+180 °C as 0-5V or 0-10V)	20 = 22:1/ 8 - 14 μm	3 = 3 m	0 = without laser pointer

Optical Specifications

Optics SF, D:S = 22:1




Optics CT LT CF, D:S = 22:1 (far field = 1.5:1)




Dimensions [mm]

Sensing head (standard)




Electronics




Accessories for TIN

Designation	Code	Description	Image
TIN-Z...	TCF	CF-lens for TIN-SS/-SH	
	TFB	Mounting bracket, fixed for TIN-SS/-SH, adjustable in one axis	
	TAB	Mounting bracket, fixed for TIN-SS/-SH, adjustable in two axis	
	HIA	USB Interfacekit for TIN-SH with Windows Software	
	MLS	OEM laser sighting aid for TIR-SH to connect to the electronics box	
	TRA	Carrier rail mounting plate for TIN-SH to connect to the electronics box	
	TF2	Mounting bracket, for TIN-SS/-SH, adjustable in one axis, probe and laser sighting aid	
	TAP	Air purge collar for TIN-SS/-SH, with mounting fork, adjustable in two axis	
	TAP2	Air purge collar for TIN-SH combinable with mounting brackets TFB/TFB/TF2	


CF-lens model TIN-ZTCF



Mounting bracket, fixed model TIN-ZTFB




Mounting bracket, adjustable in one axis model TIN-ZTF2




USB Interfacekit model TIN-ZSIA with Micro-USB plug and adapter USB-C and USB-A
(Software Download at www.kobold.com/qr/TIN)




OEM laser sighting aid model TIN-ZMLS




Mounting bracket, fixed for TIN-SS/-SH, adjustable in one axis,
Model TIN-ZTAB



Free blowing offset, with mounting fork, adjustable in two axis,
Model TIN-ZTAP



Carrier rail mounting plate,
model TIN-ZTRA



Air purge collar for TIN-SH combinable with mounting
brackets
Typ TIN-ZTAP2

